

SPEED BY SPECTRE®

The 400mph Company™

Intake Installation Instructions

P/N 9934 (red filter) - P/N 9934B (blue filter)

P/N 9934K (black filter) - P/N 9934W (white filter)

Year/Make/Model/Engine

2009-2011 Dodge RAM Trucks 5.7L HEMI



Parts List

- 1- Intake tube
- 1 - Heat shield
- 1 - hpr9892 Air filter
- 1 - 3.5" Flex Coupler
- 1 - 3.5" Coupler
- 1 - Grommet
- 1 - 29" Breather Hose
- 4 - C78-101 Clamp
- 2 - C30 Clamp
- 1 - 39" Rubber Seal
- 1 - 3.5" Velocity Stack Adapter

Tools Required:

- Ratchet
- 5/16" Nut driver
- 5/16" or 8 mm Socket

This kit comes with a high flow lifetime hpR filter. It is factory pre-oiled and ready to install.

For cleaning instructions, visit our website -

www.SpeedBySpectre.com

For filter reorders ask at the special order counter of your local parts store or call:

1-909-673-9800

ask for: P/N HPR9892 (red filter)

P/N HPR9892B (blue filter)

P/N HPR9892K (black filter)

P/N HPR9892W (white filter)



**CARB Exempt-No
Products that are not
CARB exempt are legal
in most states, but may
not be used in California
or states with similar
emissions control laws.**

Step 1

Safety first! Before you begin the installation, make sure that the vehicle is in park (or neutral for a manual transmission) with the parking brake set. Disconnect the negative battery terminal and verify that all components that are listed are present. *Note: This kit was designed and tested on a stock engine without any custom tuning done to the engine computer. Removing the battery cable may erase the programmed radio stations. The anti-theft code will need to be entered into some radios after the battery cable is connected. The anti-theft code can typically be found in the owner's manual or at your local dealership.*



Step 2
Disconnect the IAT sensor connector.



Step 3
Disconnect the PCV breather hose from the airbox lid.



Step 4
Loosen the clamp on the tube going to the throttle body. Unclip the four hold down clips on the air filter lid. Remove the intake tube and airbox lid assembly from the vehicle. Remove the stock airfilter.



Step 5
Remove the engine cover.



Step 6
Disconnect the factory PCV breather hose from the engine.



Step 7
Install the new PCV breather line supplied in the kit. Once in place securely fasten with clamp provided.



Step 8
Reinstall the engine cover. Make sure the new PCV breather line fits into notch on the engine cover.



Step 9
Install the coupler onto the throttle body. Tighten the clamp on the throttle side and make sure the intake side clamp is installed but left loose.



Step 10
Place the velocity stack adapter in the heat shield and install the supplied flex boot making sure the coupler is pushed completely against the heat shield. Once the adapter and coupler are tight against the heat shield, tighten the clamp. Make sure that the clamp for the intake tube is installed but left loose at this time. Install the air filter and dress the heat shield with rubber seal.



Step 11
Install the heat shield making sure that the slots on the heat shield are inserted into the lower factory airbox tabs. With the heat shield located in the tabs, using the 4 factory clips from the airbox, clip heat shield into position.



Step 12
Remove the IAT sensor from the factory intake tube.



Step 13
Install the grommet into the tube.



Step 14
Reinstall the factory IAT sensor.



Step 15
Install the Spectre Performance intake tube into the throttle body coupler and then into the coupler on the heat shield. Once in position fully tighten the clamps.



Step 16
Connect the new PCV breather line supplied in the kit to the new Spectre Performance intake tube. Once in place securely fasten with the clamp provided.



Step 17
Connect the IAT sensor by pushing the connector on the sensor. Once bottomed out, push the red clip towards the tube to lock in place.



Step 18

Make sure that all clamps and hardware are fully tightened. Reconnect the battery cable and start the engine and let it warm up. Shut it off and inspect the installation once more for any loose clamps, wires, or hardware. Test drive & enjoy! Your installation is now complete. Periodically check all clamps and brackets.

If you have any difficulties or questions regarding the installation of this intake system, contact the Spectre Performance Technical Department by email - Tech@spectreperformance.com or by phone (909) 673-9800 Monday thru Thursday 6:00am to 4:30pm PST.

SPEED BY SPECTRE

The 400mph Company

(909) 673-9800

www.SpeedBySpectre.com